

**Safest technology,
perfect quality.**

**Open the morning mail
faster than you can sort it.**

**Automatic letter opener
ENVELO**

Your mail is our strength



An envelope opener designed to protect the envelope's contents: Cuts a single slit quickly and safely.

Automatic envelope feed: Loading the envelopes vertically even makes it possible to open large envelopes easily.



The letter catch tray collects the envelopes in a neat vertical stack in unchanged order, and can be emptied even as the machine works.

A pressure arm guides the stack of envelopes into the separator rollers and then to the cutter, meaning there's no need to guide the envelopes by hand.

Cutting method: The cutter opens the envelope by making a precise incision into one side of the envelope very close to the envelope's edge. The contents remains untouched and safe and there are no scraps of waste paper or sharp paper edges.




Perfectly prepared:
The slit cut into the envelope offers your fingers a comfortable lip for spreading the opening and getting to the contents.

The ENVELO automatic letter opener opens envelopes by slitting one side open, producing no waste paper scraps and never damaging the envelope's contents or creating sharp paper edges.

ENVELO automatically draws a single envelope from the unsorted stack of mail, cuts the envelope open and then deposits the envelope in a tray, in the same order as loaded. Slit open right at the edge of the envelope, there's no way contents can be damaged and there are no waste paper scraps that can create jams and dust.

The simple and safe cutting principle with which the ENVELO works makes it possible to save time every day, getting the daily mail distributed faster and letting employees turn to more productive work than opening envelopes manually.



A neat, no-risk solution:
Instead of cutting a strip off, ENVELO cuts an opening in the envelope's side.

Technical data

Model type	ENVELO
Performance	300 letters/minute (if DIN C6 in length)
Envelope sizes	from 90 x 140 mm to 280 x 400 mm (DIN E4)
Envelope thickness	up to 4 mm
Noise level	58 dB(A)
Power requirement	220-240 V/50 Hz or 110 V/50 Hz/60 Hz
Dimensions (L x W x H)	400 (800, incl. letter catch tray) x 300 x 230 mm
Weight	ca. 9 kg



subject to technical modifications

Your local FP partner:

Your mail is our strength

Francotyp-Postalia AG & Co · PO Box · D- 16542 Birkenwerder
Phone: + 49/33 03/5 25-0 · Fax: +49/33 03/5 25-7 99
Internet: www.francotyp.com · E-mail: info@francotyp.com